









TECHNICAL DATA				
区	Measures (mm)	1200 x 1000 x 165		
	Weight (kg +/- 3%)	26		
	Material	Recycled HDPE or PP		
	Static load* (kg)	7000		
	Dynamic load** (kg)	2500		
目	Load in rack*** (kg)	1250		

CH	HARACTERISTICS	
	Standard color	Anthracite
	Lip (mm)	5,5
	Temperature range (°C)	-20 to +40



OPTIONS

No lip / Anti-slip strips / Special color / RFID / Forklift supporting areas

PACKAGING	(indicative values)
Packaging unit (pcs)	14
Bulk size (mm)	1200 x 1000 x 2400
Truck (pcs)	364

PERSONALIZED MARKING	(consult conditions)

Silkscreen printing / Heat stamped / Mold engraving











We recommend testing the pallet before use.

* Static load: Uniformly distributed load which the pallet can support when placed on a flat, horizontal rigid surface, at a temperature of approximately 20°C. ** Dynamic load: Uniformly distributed load which the pallet can support when transported or manoeuvred on a conventional forklift or pallet truck, at a temperature of approximately 20°C. *** Load in rack: Uniformly distributed load which the pallet can support when resting on the skids on its short side on a standard rack, at a temperature of approximately 20°C.

> The indicated values are approximate and based on experience and practical cases. Any deterioration or different loading, temperature or storage method conditions, can cause this data to vary. We reserve the right to modify any information provided herein without prior notice.